

Explorer 5



Ergonomic Design


I need a portable, light-weight ultrasound which is easy to go,easy to diagnose, easy to operate with sufficient measurement packages.

- Independent angle 15" LED
- (0° 30° tilted)
- Lightweight (7.5Kg / 16.5lbs)
- Dual transducer ports (Built-in)
- Probe holders
- Removable battery, 120 minutes in active mode

Theft-proof lock


- Dediceted adapter Space
- Printer socket
- Accessory box
- Trolley height adjustable (Three levels available)






Auto IMT

Automatically traces the intima, and measures the thickness of the intima. This allows you to measure the intima faster, more easily and more accurately.




Up to 18MHz High Frequency Linear Probe

Our high frequency linear probe provides unparalleled detail resolution and superior contrast resolution with up to 18 MHz imaging frequency.



Q-image


These innovative algorithms have strengthened the image enhancement results significantly. Advanced chipset is used to ensure fast frame rate.




Super Needle

With Super Needle, clinicians can see needle inside tissue more clearly during medical procedures.


Needle angle up to +30°




CCA, ICA, ECA, B Mode




Popliteal Artery and Vein




Fingertips Vessle, C Mode



Fingertips Vessle, PW Mode



Knee, 4B Mode



Elbow Joint, 4B Mode

TX PX

Traditional Dual Beam

Hosmed Quad Beam

BigHt 8/AL() 12.55

Q-beam

General Imaging

Compared to the traditional dual-beam former on most ultrasound machines, the Explorer 5 uses quad-beam technology for ultrasound signal receiving.

Doubles the volume of signals received from traditional methods, increasing image resolution and generating more accurate images.

Produces higher frame rates, ensuring better diagnostic confidence and efficiency, especially for moving organs.

Elastography

Elastography displays tissue stiffness in real time to provide doctors with additional diagnostic information when scanning organs like liver and breast.

FHI



FHI is an innovative harmonic imaging technology that uses multiple transmission and receiving methods based on the patients' size and weight. This allows the Explorer 5 to maintain image resolution when imaging larger patients.


Traditional Tissue Harmonics and Phased Harmonics compromise image quality and resolution when penetration is increased. Hosmed FHI technology greatly improves diagnostic abilities and clinical confidence in larger, difficult-to-image patients.




HIP Graf



Gallbladder Stone, B mode




Abdomen, 4B Mode



Pancreas, B/BC Mode



Umbilical Cord, C Mode



Aorta Artery, PW Mode



2.0 - 6.8 Mhz Converx C3-E



4.0-15.0 Mhz Linear L7-E



7.0-18.0 mhz (with FHI) Linear L12-E



4.0-15.0 Mhz Linear L7W-E



4.0 12.0 Mhz Transvaginal V6-E



4.0 15.0 Mhz Transvaginal V7-E



4.0 15.0 Mhz Trans-Rectal L&7-E



2.0-6.8 Mhz Micro-Convex MC3-E



4.0-12.0 Mhz Micro-Convex MC6-E



4.0-10.7 Mhz Micro-Convex MC5-E

Specifications

- B, 2B, 4B,B/M
- CFM
- PW
- PD, DPD(Direction Power Doppler)
- Duplex, Triplex
- Trapezoidal
- ChromaB/M/ PW
- Super Needle (option)
- 2D steer
- Auto IMT
- HIP Graf
- DICOM (option)

Comprehensive Applications

- OB/GYN
- Urology
- Pediatric
- Radiology
- Internal Medicine
- Small Parts
- General Imaging
- Vascular
- Intensive Care
- Emergency
- MSK

Image Processing Technologies

- FHI
- Q-beam
- Q-flow
- Q-image
- X-contrast
- SRA
- Compound Image

Accessories

- Footswitch
- Trolley
- Suitcase
- Video Printer
- PC Printer





3403 NW 82nd Avenue, Suite 102 E. Doral, Florida 33122. USA